MATERIAL SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI and Canadian WHMIS Standards

PART I What is the material and what do I need to know in an emergency?

1. PRODUCT IDENTIFICATION

TRADE NAME (AS LABELED):
CHEMICAL NAME/CLASS:
PRODUCT NUMBER:
PRODUCT USE:

QUALI-PHITE F Inorganic Salt Mixture 83472-1-53883 Fungicide

<u>SUPPLIER/MANUFACTURER'S NAME:</u> <u>ADDRESS</u>: Control Solutions, Inc. 5903 Genoa Red Bluff Pasadena, TX 77507

EMERGENCY PHONE: BUSINESS PHONE: FAX PHONE: SafetyCall[®] (866) 897-8050

(281) 892-2500

(281) 892-2501

DATE OF PREPARATION:

September 15, 2012

2. COMPOSITION and INFORMATION ON INGREDIENTS

CHEMICAL NAME	% w/w	EXPOSURE LIMITS IN AIR					
		ACGIH		OSHA			
		TLV mg/m ³	STEL mg/m ³	PEL mg/m ³	STEL mg/m ³	IDLH mg/m ³	OTHER
Organic Acid Salt	5 - 10	NE	NE	NE	NE	NE	NE
Organic Acid	> 1	NE	NE	NE	NE	NE	NE
Organic Compound (exposure limits are for mists of this substance)	> 1	10	NE	15 (Total); 5 (Respirable fraction) 10 (Total) (vacated 1989 PEL)	NE	NE	NE
Proprietary Potassium Compounds	> 1	NE	NE	NE	NE	NE	NE
Water and other components. Each of the other components are present in less than 1 percent concentration (or 0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens).	Balance	None of the other components contribute significant, additional, hazards at the concentrations present in this product.					

NE = Not Established C = Ceiling Limit See Section 16 for Definitions of Terms Used

NOTE (1): ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-1993 format.

NOTE (2): Though information in this document is proprietary, ALL pertinent hazard information is provided in the following MSDS sections, per the requirements of the U.S. Federal Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Identification System. This information will be released when the conditions of the Standard are met.

3. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW: This is a water clear solution with a soap-like odor. This product presents a slight health hazard (in terms of irritation of contaminated skin, eyes, or mucous membranes). This product presents no significant flammability or reactivity hazards. Emergency responders must wear the personal protective equipment suitable for the situation to which they are responding.

SYMPTOMS OF OVEREXPOSURE BY ROUTE OF EXPOSURE: The chief routes of overexposure to this product are via

inhalation of mists or sprays generated by this product and contact with skin or eyes. The symptoms of overexposure, via route of entry, are as follows:

<u>INHALATION</u>: Inhalation of sprays, aerosols, or mists of this solution may be irritating to the nose, throat and exposed mucous membranes. Symptoms of such exposure may include coughing, sneezing, and sore throat. Symptoms are generally alleviated when overexposure ends.

<u>CONTACT WITH SKIN or EYES</u>: Contact with skin may cause irritation and reddening of exposed tissue. The Organic Acid component of this solution is a potential allergen. Prolonged or repeated skin contact can lead to the development of allergy-like symptoms (e.g., dermatitis). Contact with eyes will lead to tearing, pain, reddening, and irritation.

<u>SKIN ABSORPTION</u>: Skin absorption is not anticipated to be a significant route of overexposure to this product.

<u>INGESTION</u>: Though not a likely route of occupational exposure, ingestion will lead to irritation of the throat, esophagus, and other tissues of the digestive system. Symptoms of such exposure would include coughing, nausea, vomiting, and diarrhea.

<u>INJECTION</u>: Injection of this product, via puncture with a contaminated object, will lead to a burning sensation, reddening, and swelling around the site of injection.

HEALTH EFFECTS OR RISKS FROM EXPOSURE: An Explanation in Lay Terms.

ACUTE: Symptoms of short-term exposures would include pain, reddening, and irritation of exposed tissue. Severe inhalation or ingestion overexposure may be harmful.

CHRONIC: Prolonged or repeated over-exposures to this product via skin contact may lead to dermatitis and other allergylike skin reactions. Refer to Section 11 (Toxicology Information) for further information on the components of this solution.

TARGET ORGANS: Skin and eyes.

4. FIRST-AID MEASURES


<u>SKIN EXPOSURE</u>: If the product contaminates the skin, decontaminate the affected area with running water. The minimum recommended flushing time is at least 15 minutes, especially if adverse skin reactions occur. If necessary, remove exposed or contaminated clothing, taking care not to contaminate eyes.

<u>EYE EXPOSURE</u>: If this product enters the eyes, open the contaminated individual's eyes while under gentle running water. Use sufficient force to open eyelids. Have the contaminated individual "roll" eyes. <u>Minimum</u> flushing is for 15 minutes.

<u>INHALATION</u>: If mists or sprays of this product are inhaled, remove the contaminated individual to fresh air. If necessary, use artificial respiration to support vital functions. Remove or cover gross contamination to avoid exposure to rescuers.

<u>INGESTION</u>: If this product is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, do not induce vomiting. Victim should drink milk, egg whites, or large quantities of water. Never induce vomiting or give diluents (milk or water) to someone who is <u>unconscious</u>, having convulsions, or unable to swallow.

Contaminated individuals must be taken for medical attention if any adverse reaction occurs. Rescuers should be taken for medical attention, if necessary. Take a copy of the label and MSDS to physician or health professional with victim.



See Section 16 for Definition of Ratings

5. FIRE-FIGHTING MEASURES

<u>FLASH POINT</u>: Not applicable. <u>AUTOIGNITION TEMPERATURE</u>: Not applicable. FLAMMABLE LIMITS (in air by volume, %):

> Lower (LEL): Not applicable. Upper (UEL): Not applicable.

FIRE EXTINGUISHING MATERIALS:

Water Spray: YES	Carbon Dioxide: YES
Foam: YES	Dry Chemical: YES
Halon: YES	Other: Any "ABC" Class.

<u>UNUSUAL FIRE AND EXPLOSION HAZARDS</u>: When involved in a fire and exposed to extremely high temperatures, the components of this product will decompose to produce irritating vapors and toxic gases (e.g., phosphorous oxides, phosphine, carbon monoxide, ammonia, and carbon dioxide).

Explosion Sensitivity to Mechanical Impact: Not applicable. Explosion Sensitivity to Static Discharge: Not applicable.

<u>SPECIAL FIRE-FIGHTING PROCEDURES</u>: Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

6. ACCIDENTAL RELEASE MEASURES

<u>RELEASE RESPONSE</u>: In case of a release, clear the affected area and protect people. Uncontrolled releases should be responded to by appropriately trained personnel in proper personal protective equipment, using pre-planned procedures.


In terms of small, incidental releases (e.g., 1 gallon from a leaking container), the minimum personal protective equipment should be as follows: gloves, goggles, and appropriate body protection (e.g., boots, Tyvek suit). For large releases (e.g. 30-gallon drum), the minimum personal protective equipment should be Level C: triple-gloves (rubber gloves and nitrile gloves, over latex gloves), chemically resistant suit and boots, hard-hat, and an Air-Purifying respirator with a high-efficiency particulate filter. In the event of a spill in which excessive amounts of mists are generated, or one in which the level of oxygen is below 19.5% or is unknown, the minimum equipment should be Level B: triple-gloves (rubber gloves and nitrile gloves, over latex gloves), chemically resistant suit and boots, hard-hat, and Self-Contained Breathing Apparatus. If necessary, dike the spill to prevent releases from contaminating environmentally sensitive areas. Absorb spilled liquid with polypads or other suitable absorbent materials. Rinse area thoroughly with water. Decontaminate the area thoroughly. Place all spill residue in an appropriate container and seal. Reuse this product, or dispose of in accordance U.S. Federal, State, or local procedures and appropriate Canadian standards (see Section 13, Disposal Considerations).

PART III How can I prevent hazardous situations from occurring?

7. HANDLING and STORAGE

<u>WORK AND HYGIENE PRACTICES</u>: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors or mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

STORAGE AND HANDLING PRACTICES -- NON-BULK CONTAINERS: All employees who handle this material should be trained to handle it safely. Open containers and drums slowly, on a stable surface. Open drum bunks carefully, to relieve any pressure build-up which may have developed during storage. All containers of this product must be properly labeled. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Store away from incompatible materials (see Section 10, Stability and Reactivity). Material should be stored in secondary containers or in a diked area, as appropriate. Keep container tightly closed when not in use. Inspect all incoming containers before storage to ensure that containers are properly labeled and are not damaged.



7. HANDLING and STORAGE (Continued)

STORAGE AND HANDLING PRACTICES -- BULK CONTAINERS: Bulk containers (e.g., 250 gallon "mini-bulk" tanks) holding this product should be loaded and unloaded in strict accordance with container manufacturer's recommendation and all established on-site safety procedures. Appropriate personal protective equipment must be used (see Section 8, Engineering Controls and Personal Protection). All transfer and dilution equipment must be inspected prior to each use. Transfer and dilution operations must be attended at all times. Hoses must be verified to be clean and free of incompatible chemicals prior to connection to the tank. Valves and hoses must be verified to be in the correct positions prior to starting transfer and dilution operations.

<u>PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT</u>: Follow practices indicated in Section 6 (Accidental Release Measures). Make certain that application equipment is locked and tagged-out safely, if necessary. Collect all rinsates and dispose of in accordance U.S. Federal, State, or local procedures and appropriate Canadian standards (see Section 13, Disposal Considerations).

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

<u>VENTILATION AND ENGINEERING CONTROLS</u>: Use with adequate ventilation to prevent inhalation of sprays or mists. All operations should be directed at minimizing the generation of aerosols, sprays, or mists. Eyewash stations/safety showers should be near areas where this product is used or sprayed.

<u>RESPIRATORY PROTECTION</u>: None required under normal circumstances of use. If operations generate aerosols, mists, or sprays which cause exposures in excess of the guidelines listed in Section 2 (Composition and Information on Ingredients), respiratory protection may be needed (e.g., air-purifying respirator with a high efficiency particulate filter) and must comply with the U.S. Federal OSHA Standard (29 CFR 1910.134), applicable U.S. State regulations, or the appropriate standards of Canada and its Provinces.

<u>EYE PROTECTION</u>: Splash goggles or safety glasses. Wear face shield for operations involving more than 5 gallons of this solution in which splashes or sprays can be generated.

HAND PROTECTION: Wear Neoprene gloves for routine industrial use. Use triple gloves for spill response, as stated in Section 6 (Accidental Release Measures) of this MSDS.

BODY PROTECTION: Use body protection appropriate for task (i.e. cover-alls, or rubber apron).

9. PHYSICAL and CHEMICAL PROPERTIES

<u>RELATIVE VAPOR DENSITY (air = 1)</u>: Not established DENSITY: 1.53 g/cc

<u>SOLUBILITY IN WATER</u>: Completely soluble. <u>VAPOR PRESSURE, mm Hg @ 20°C (68°F)</u>: Not established. <u>ODOR THRESHOLD</u>: Not established. $\frac{\text{EVAPORATION RATE (n-BuAc = 1):}{\text{MELTING/FREEZING POINT:} < 0^{\circ}\text{C} (32^{\circ}\text{F})}$ $\frac{\text{BOILING POINT:}{\text{DOINT:}} > 100^{\circ}\text{C} (212^{\circ}\text{F})$ $\frac{\text{pH:}}{\text{PH:}} 6.9$

COEFFICIENT OF OIL/WATER DISTRIBUTION (PARTITION COEFFICIENT): Not available.

<u>APPEARANCE AND COLOR</u>: This is a clear, colorless, solution with a faint to slight odor. <u>HOW TO DETECT THIS SUBSTANCE (warning properties)</u>: The appearance and odor may act as distinguishing characteristics of this product.

10. STABILITY and REACTIVITY

STABILITY: Stable.

<u>DECOMPOSITION PRODUCTS</u>: When exposed to extremely high temperatures, the components of this product will decompose to produce irritating vapors and toxic gases (e.g., phosphorous oxides, phosphine, carbon monoxide, ammonia, and carbon dioxide).

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Strong bases, strong oxidizers, strong reducers, and waterreactive materials.

HAZARDOUS POLYMERIZATION: Will not occur.

<u>CONDITIONS TO AVOID</u>: Exposure to extreme temperatures and incompatible materials.

11. TOXICOLOGICAL INFORMATION

TOXICITY DATA: The specific toxicology data available for components greater than 1% in concentration are as follows.

ORGANIC ACID:

- Skin-Rabbit, adult 500 mg/24 hours; Moderate irritation effects
- Eye effects-Rabbit, adult 750 mg/24 hours; Severe irritation effects Oral-Rat LD₅₀: 3 g/kg Intraperitoneal-Rat LD₅₀: 883 mg/kg
- Subcutaneous-Rat LD_{50} : 5500 mg/kg Oral-Mouse LD_{50} : 5040 mg/kg Intraperitoneal-Mouse LD_{50} : 903 mg/kg Subcutaneous-Mouse LD_{50} : 2700 mg/kg Intravenous-Mouse LD_{50} : 42 mg/kg Oral-Rabbit, adult LDLo: 7000 mg/kg Intravenous-Rabbit, adult LD_{50} : 330 mg/kg

 $\begin{array}{l} \textbf{ORGANIC COMPOUND:} \\ Skin Irritancy (rabbit) = 500 mg/ 24 hours; mild \\ Eyes Irritancy (rabbit) = 126 mg; mild \\ Eyes Irritancy (rabbit) = 500 mg/ 24 hours; mild \\ DNA Inhibition System (lymphocytes, human) = 200 mmol/L TDLo (intratesticular, rat) = 1600 mg/kg; reproductive effects \\ TDLo (human, oral) = 1428 mg/kg; central nervous system, gastrointestinal effects \\ LD_{50} (intraperitoneal, rat) = 4420 mg/kg \\ LD_{50} (oral, mouse) = 4090 mg/kg \\ LD_{50} (subcutaneous, mouse) = 8982 mg/kg \\ LD_{50} (subcutaneous, mouse) = 91 mg/kg \end{array}$

 $\begin{array}{l} \textbf{ORGANIC COMPOUND (continued):} \\ \textbf{LD}_{50} (intravenous, mouse) = 4250 mg/kg \\ \textbf{LD}_{50} (intravenous, rabbit) = 53 g/kg \\ \textbf{LD}_{50} (oral, guinea pig) = 7750 mg/kg \end{array}$

- **PROPRIETARY POTASSIUM COMPOUNDS:** There are currently no toxicology data available for these components of the product.
- **ORGANIC ACID SALT:** There are currently no toxicology data available for this component of the product.

<u>SUSPECTED CANCER AGENT</u>: This product's components are not found on the following lists: U.S. FEDERAL OSHA Z LIST, NTP, IARC, and CAL/OSHA and therefore are neither considered to be nor suspected to be cancer-causing agents by these agencies

IRRITANCY OF PRODUCT: This product can be irritating to contaminated tissue upon prolonged or repeated exposure.

<u>SENSITIZATION TO THE PRODUCT</u>: The Organic Acid, which is a component of this product, is a potential skin sensitizer. Prolonged or repeated skin contact can result in the development of allergy-like skin reactions (e.g., dermatitis, rashes).

<u>REPRODUCTIVE TOXICITY INFORMATION</u>: Listed below is information concerning the effects of this product and its components on the human reproductive system.

<u>Mutagenicity</u>: Human mutation data are available for the Organic Compound (a component of this product); these data were obtained during clinical studies on specific human tissues exposed to high doses of this compound.

Embryotoxicity: This product is not reported to produce embryotoxic effects in humans.

<u>Teratogenicity</u>: This product is not reported to cause teratogenic effects in humans.

<u>Reproductive Toxicity</u>: This product is not reported to cause reproductive effects in humans. Clinical studies on test animals exposed to relatively high doses of the Organic Compound (a component of this product) provided reproductive toxicity data.

A <u>mutagen</u> is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An <u>embryotoxin</u> is a chemical which causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A <u>teratogen</u> is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A <u>teratogen</u> is a <u>reproductive toxin</u> is any substance which interferes in any way with the reproductive process.

<u>ACGIH BIOLOGICAL EXPOSURE INDICES</u>: Currently, there are no ACGIH Biological Exposure Indices (BEIs) associated with the components of this product.

<u>MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE</u>: Preexisting respiratory problems, dermatitis, and other skin disorders can be aggravated by exposure to this product.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and eliminate overexposure.

12. ECOLOGICAL INFORMATION

WORK PRACTICES MUST PREVENT UNINTENTIONAL, ENVIRONMENTAL RELEASES.

<u>ENVIRONMENTAL STABILITY</u>: The components of this solution are relatively stable, but will decompose over time to generate other inorganic compounds. The following environmental data are available for the components of this product:

ORGANIC ACID: Water Solubility = 59.2% (20°C); 84% (100°C). Biological Oxygen Demand (BOD): 40%, 5 days; 60%, 10-20 days. The Organic Acid biodegrades quite rapidly. It is dangerous to aquatic life in high concentrations. Lowers pH in water but does not dissociate to any great extent.

ORGANIC COMPOUND: Water Solubility = Miscible. Log K_{ow} = -1.76. Bioconcentration potential is low. 5-Day Biological Oxygen Demand = 0.54 p/p; 10 day BOD = 0.98 p/p; 20 Day BOD = 1.0 p/p:

12. ECOLOGICAL INFORMATION (Continued)

<u>EFFECT OF MATERIAL ON PLANTS or ANIMALS</u>: This solution is irritating to contaminated animals. Refer to Section 11 (Toxicology Information) for information on this product's components and their effects on test animals. This product is a fertilizer. Releases of large quantities into an area can substantially alter the nutrient composition affect terrestrial plant life.

<u>EFFECT OF CHEMICAL ON AQUATIC LIFE</u>: This product is a fertilizer. Releases of large quantities into a body of water can substantially alter the nutrient composition affect aquatic plant and animal life. The following aquatic toxicity information is available for the components of this product.

ORGANIC ACID:

Food Chain Concentration Potential: Very Low

Aquatic TLm (immersion-shore crab) 48 hrs, salt water 160 ppm (immersion-goldfish) 4 hr, fresh water 894 ppm killed Waterfowl toxicity: No data available

TLm (immersion, shore crab) = 160 ppm/ 48 hours/ salt water

TLm (immersion, goldfish) = 894 ppm/ 4 hours/ fresh water/ killed

ORGANIC COMPOUND:

LC₅₀ (*Pimephales promelas*, fathead minnow) = 44000 mg/L LC₅₀ (*Carassiius auratus*, goldfish) = 5000 mg/L EC₀ (Pseudomonas putida, bacteria) >10,000 mg/L/ 16 hours EC₀ (Microcystis aeruginosa, algae) = 2,900 mg/L/ 8 days EC₀ (Scenedesmus quadricauda, green algae) >10,000 mg/L/ 7 days EC₀ (Entosiphon sulcatum, protozoa) = 3,200 mg/L/ 72 hours EC₀ (Uronema parduczi Chatton-Lwoff, protozoa) >10,000 mg/L LC₅₀ (goldfish) 5,000 mg/L/ 24 hours

13. DISPOSAL CONSIDERATIONS

<u>PREPARING WASTES FOR DISPOSAL</u>: Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations or those of Canada and its Provinces. This product, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority.

U.S. EPA WASTE NUMBER: Not applicable.

14. TRANSPORTATION INFORMATION

THIS MATERIAL IS NOT HAZARDOUS, PER 49 CFR 172.101, U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: HAZARD CLASS NUMBER and DESCRIPTION:

UN IDENTIFICATION NUMBER:

PACKING GROUP:

DOT LABEL(S) REQUIRED:

Not applicable. Not applicable. Not applicable. Not applicable.

Not applicable.

NORTH AMERICAN EMERGENCY RESPONSE GUIDE NUMBER - 1996: Not applicable.

MARINE POLLUTANT: No component of this product is listed as a DOT Marine Pollutant (49 CFR 172.101, Appendix B).

TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: THIS MATERIAL IS NOT CONSIDERED AS DANGEROUS GOODS.

15. REGULATORY INFORMATION

ADDITIONAL U.S. REGULATIONS:

<u>U.S. SARA REPORTING REQUIREMENTS</u>: The components of this product are not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization, as follows.

U.S. SARA THRESHOLD PLANNING QUANTITY: Not applicable.

U.S. CERCLA REPORTABLE QUANTITY (RQ): Not applicable.

U.S. TSCA INVENTORY STATUS: The components of this product are listed on the TSCA Inventory.

OTHER U.S. FEDERAL REGULATIONS: Not applicable.

U.S. STATE REGULATORY INFORMATION: Components of this product are covered under specific State regulations, as denoted below:

Alaska - Designated Toxic and Hazardous Substances: Mists of Organic Compound. California - Permissible Exposure Limits for Chemical Contaminants: Mists of Organic Compound. Florida - Substance List: No.

Illinois - Toxic Substance List: Mists of Organic Compound.

Kansas - Section 302/313 List: No.

Massachusetts - Substance List: No.

- ous Michigan Critical Materials Register: No. Minnesota - List of Hazardous Substances: for Mists of Organic Compound. nic Missouri - Employer Information/Toxic Substance List: Mists of Organic Compound. New Jersey - Right to Know Hazardous of Substance List: No. North Dakota - List of Hazardous Chemicals, Reportable Quantities: No.
- Pennsylvania Hazardous Substance List: Glycerin.

Rhode Island - Hazardous Substance List: Mists of Organic Compound.

Texas - Hazardous Substance List: No.

West Virginia - Hazardous Substance List: No.

Wisconsin - Toxic and Hazardous Substances: No.

15. REGULATORY INFORMATION (Continued)

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): No component of this product is on the California Proposition 65 lists.

ANSI LABELING: CAUTION! MAY CAUSE SKIN, EYE AND RESPIRATORY SYSTEM IRRITATION. PROLONGED SKIN CONTACT MAY RESULT IN ALLERGIC REACTIONS. HARMFUL IF SWALLOWED. FOR AGRICULTURAL USE ONLY. KEEP AWAY FROM CHILDREN. Avoid contact with skin, eyes, and clothing. Avoid prolonged skin contact. Wash thoroughly after handling. Use in well-ventilated area. Use gloves, safety goggles, and appropriate body protection. **FIRST-AID:** In case of skin or eye contact, flush with copious amounts of water. Recommended flushing time is for 15 minutes. If inhaled, remove to fresh air. If ingested, do not induce vomiting. If adverse reactions occur, get medical attention. **IN CASE OF FIRE:** Use water fog, dry chemical, CO₂ or "alcohol" foam. **IN CASE OF SPILL:** Absorb with an inert material (i.e. polypads), then place in a suitable container. Consult Material Safety Data Sheet.

ADDITIONAL CANADIAN REGULATIONS:

CANADIAN DSL/NDSL INVENTORY STATUS: The components of this product are on the DSL/NDSL Lists.

OTHER CANADIAN REGULATIONS: Not applicable.

CANADIAN ENVIRONMENTAL PROTECTION AGENCY (CEPA) PRIORITIES SUBSTANCES LISTS: Not applicable

CANADIAN WHMIS SYMBOLS:

Class D2B: Other Toxic Effects



16. OTHER INFORMATION

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Biagro Western Sales, Inc. assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Biagro Western Sales, Inc. assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these which are commonly used include the following:

CAS #: This is the Chemical Abstract Service Number which uniquely identifies each constituent. It is used for computer-related searching.

EXPOSURE LIMITS IN AIR:

ACGIH - American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits. **TLV** - Threshold Limit Value - an airborne concentration of a substance which represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour Time Weighted Average (**TWA**), the 15-minute Short Term Exposure Limit, and the instantaneous Ceiling Level (**C**). Skin absorption effects must also be considered.

OSHA - U.S. Occupational Safety and Health Administration.

PEL - Permissible Exposure Limit - This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL," is placed next to the PEL which was vacated by Court Order. IDLH - Immediately Dangerous to Life and Health - This level represents a concentration from which one can escape within 30minutes without suffering escape-preventing or permanent injury. The DFG -MAK is the Republic of Germany's Maximum Exposure Level, similar to the U.S. PEL. NIOSH is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (OSHA). NIOSH issues exposure guidelines called Recommended Exposure Levels (RELs). When no exposure guidelines are established, an entry of NE is made for reference.

HAZARD RATINGS:

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: Health Hazard: 0 (minimal acute or chronic exposure hazard); 1 (slight acute or chronic exposure hazard); 2 (moderate acute or significant chronic exposure hazard); 3 (severe acute exposure hazard; onetime overexposure can result in permanent injury and may be fatal); 4 (extreme acute exposure hazard; onetime overexposure can be fatal). Flammability Hazard: 0 (minimal hazard); 1 (materials that require substantial pre-heating before burning); 2 (combustible liquid or solids; liquids with a flash point of 38-93°C [100-200°F]); 3 (Class IB and IC flammable liquids with flash points below 38°C [100°F]); 4 (Class IA flammable liquids with flash points below 23°C [73°F] and boiling points below 38°C [100°F]. Reactivity Hazard: 0 (normally stable): 1 (material that can become unstable at elevated temperatures or which can react slightly with water); 2 (materials that are unstable but do not detonate or which can react violently with water); 3 (materials that can detonate when initiated or which can react explosively with water); 4 (materials that can detonate at normal temperatures or pressures).

NATIONAL FIRE PROTECTION ASSOCIATION: <u>Health Hazard</u>: 0 (material that on exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials); 1 (materials that on exposure under fire conditions could cause irritation or minor residual injury); 2 (materials that on intense or continued exposure under fire conditions could cause irritation or possible residual injury); 3 (materials that can on short exposure could cause serious temporary or residual injury); 4 (materials that under very short exposure causes death or major residual injury). Flammability Hazard and Reactivity Hazard: Refer to definitions for "Hazardous Materials Identification System".

FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). <u>Flash Point</u> - Minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. <u>Autoignition Temperature</u>: The minimum temperature required to initiate combustion in air with no other source of ignition. <u>LEL</u> - the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. <u>UEL</u> - the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

TOXICOLOGICAL INFORMATION:

Human and Animal Toxicology: Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms used in this section are: LD50 - Lethal Dose (solids & liquids) which kills 50% of the exposed animals; LC50 - Lethal Concentration (gases) which kills 50% of the exposed animals; ppm concentration expressed in parts of material per million parts of air or water: ma/m³ concentration expressed in weight of substance per volume of air; mg/kg quantity of material, by weight, administered to a test subject, based on their body weight in kg. Other measures of toxicity include TDLo, the lowest dose to cause a symptom and TCLo the lowest concentration to cause a symptom; TDo, LDLo, and LDo, or TC, TCo, LCLo, and LCo, the lowest dose (or concentration) to cause lethal or toxic effects. Cancer Information: The sources are: IARC - the International Agency for Research on Cancer; NTP - the National Toxicology Program, RTECS - the Registry of Toxic Effects of Chemical Substances, OSHA and CAL/OSHA. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used. Other Information: BEI - ACGIH Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV. Ecological Information: EC is the effect concentration in water. BCF = Bioconcentration Factor, which is used to determine if a substance will concentrate in lifeforms which consume contaminated plant or animal matter. Coefficient of Oil/Water Distribution is represented by log Kow or log Koc and is used to assess a substance's behavior in the environment.

REGULATORY INFORMATION:

This section explains the impact of various laws and regulations on the material. U.S.: EPA is the U.S. Environmental Protection Agency. DOT is the U.S. Department of Transportation. SARA is the Superfund Amendments and Reauthorization Act. TSCA is the U.S. Toxic Substance Control Act. CERCLA (or Superfund) refers to the Comprehensive Environmental Response, Compensation, and Liability Act. Labeling is per the American National Standards Institute (ANSI Z129.1). CANADA: CEPA is the Canadian Environmental Protection Agency. WHMIS is the Canadian Workplace Hazardous Materials Information System. TC is Transport Canada. DSL/NDSL are the Canadian Domestic/Non-Domestic Substances Lists.